



BODY REAR DETAIL

FEATURES:

- QUICK HAND INDEXING WITH CHOICE OF THREE, FOUR, OR FIVE OUTLET TURRET.
- ALLOWS FOR RAPID CHANGE OF SPRAY TIPS WITH USE OF QUICK TEEJET CAPS.
- POSITIVE SHUT-OFF BETWEEN EACH SPRAY POSITION.
- BODY DESIGNED TO FIT INTO STANDARD CAM-LOC STYLE QUICK COUPLERS.
- LOCATING NIB KEEPS BODY PROPERLY ORIENTED IN CAM-LOC FITTING.
- BODY ASSEMBLY CAN BE INSERTED IN PLACE OF QCK AND QCTF FLOODJET TIPS TO ALLOW FOR USE OF SMALLER CAPACITY SPRAY TIPS.
- ALLOWS FOR RAPID CHANGE OVER FROM HIGH VOLUME FERTILIZER APPLICATIONS TO LOWER VOLUME PESTICIDE APPLICATIONS.
- MADE OF CORROSION RESISTANT MATERIALS.
- STANDARD O-RINGS MADE OF EPDM, TEFLON FILLED EPDM, AND VITON.
- OPTIONAL O-RINGS MADE OF VITON AND TEFLON FILLED VITON.
- MAXIMUM OPERATING PRESSURE – 300 PSI (20 bar).
- FLOW RATE: 2.25 GPM (8.5 l/min) WITH A 5 PSI PRESSURE DROP
- IF TURRET BECOMES DIFFICULT TO TURN REMOVE E-CLIP, SLIDE TURRET OFF BODY, AND LUBRICATE O-RINGS AND SEAL WITH A SILICONE BASED LUBRICANT.

HOW TO ORDER:

QC363-NYB QUICK TEEJET CAM-LOC NOZZLE BODY ASSEMBLY WITH 3 OUTLETS
 QC364-NYB QUICK TEEJET CAM-LOC NOZZLE BODY ASSEMBLY WITH 4 OUTLETS
 QC365-NYB QUICK TEEJET CAM-LOC NOZZLE BODY ASSEMBLY WITH 5 OUTLETS

QC363-NYB-VI QUICK TEEJET CAM-LOC NOZZLE BODY ASSEMBLY WITH 3 OUTLETS (VITON DIAPHRAGM AND O-RINGS)
 QC364-NYB-VI QUICK TEEJET CAM-LOC NOZZLE BODY ASSEMBLY WITH 4 OUTLETS (VITON DIAPHRAGM AND O-RINGS)
 QC365-NYB-VI QUICK TEEJET CAM-LOC NOZZLE BODY ASSEMBLY WITH 5 OUTLETS (VITON DIAPHRAGM AND O-RINGS)

DESCRIPTION:

**QC360 QUICK TEEJET®
TURRET NOZZLE BODY
WITH CAM-LOC ADAPTER**



Spraying Systems Co.®

Spray Nozzles and Accessories
 P.O. Box 7900 – Wheaton, IL 60189-7900

Rev. No.

Ref.

DATA SHEET

QC360

SHEET OF