

StreamJet SJ3-VR VARIABLE RATE

Typical Applications



**FERTILIZER
BROADCAST
EXCELLENT**



**DRIFT
CONTROL
EXCELLENT**




FERTILIZER NOZZLES

FEATURES

- The SJ3-VR line of variable rate fertilizer spray tips feature a variable diameter orifice that produces a wide range of flow rates—it's like having five tips in one.
- Allows for a wider range of ground speeds and/or application rates from a single tip for improved productivity.
- Are also ideal for variable rate prescription map applications.
- SJ3-VR tip produces three identical fluid streams for excellent distribution quality in directed applications.
- Solid stream pattern minimizes leaf burn and virtually eliminates drift.
- Acetal body and deflector plate construction for good wear life and chemical resistance.
- Simple, elastomer (EPDM) variable orifice for reliable operation.
- SJ3-VR are intended for use with flow meter based control systems only.
- Multiple capacities available for a wider range of application rates.

SPRAY PATTERN



OPTIMUM SPACING AND SPRAY HEIGHT

HEIGHT	SPACING
50 cm	50 cm
75 cm	75 cm
100 cm	100 cm

*For best spray distribution maintain a 1:1 ratio of tip height to tip spacing.

RECOMMENDED PRESSURE RANGE



MATERIALS AVAILABLE



HOW TO ORDER

Polymer with VisiFlo® color-coding

S J 3 - V R - X 2 . 0

Tip
Type

Material
Code

Capacity
Size

StreamJet SJ3-VR VARIABLE RATE

FERTILIZER NOZZLES

TIP PART NO.	bar	CAPACITY ONE TIP IN l/min	APPLICATION RATE FOR 35 cm SPRAY TIP SPACING											APPLICATION RATE FOR 50 cm SPRAY TIP SPACING										
			l/ha											l/ha										
			4 km/h	6 km/h	8 km/h	10 km/h	12 km/h	16 km/h	20 km/h	25 km/h	30 km/h	35 km/h	4 km/h	6 km/h	8 km/h	10 km/h	12 km/h	16 km/h	20 km/h	25 km/h	30 km/h	35 km/h		
SJ3-VR-X0.5	1.5	0.51	219	146	109	87.4	72.9	54.6	43.7	35.0	29.1	25.0	153	102	76.5	61.2	51.0	38.3	30.6	24.5	20.4	17.5		
	2.0	0.58	249	166	124	99.4	82.9	62.1	49.7	39.8	33.1	28.4	174	116	87.0	69.6	58.0	43.5	34.8	27.8	23.2	19.9		
	2.5	0.64	274	183	137	110	91.4	68.6	54.9	43.9	36.6	31.3	192	128	96.0	76.8	64.0	48.0	38.4	30.7	25.6	21.9		
	3.0	0.71	304	203	152	122	101	76.1	60.9	48.7	40.6	34.8	213	142	107	85.2	71.0	53.3	42.6	34.1	28.4	24.3		
	3.5	0.79	339	226	169	135	113	84.6	67.7	54.2	45.1	38.7	237	158	119	94.8	79.0	59.3	47.4	37.9	31.6	27.1		
	4.0	0.87	373	249	186	149	124	93.2	74.6	59.7	49.7	42.6	261	174	131	104	87.0	65.3	52.2	41.8	34.8	29.8		
	5.0	1.06	454	303	227	182	151	114	90.9	72.7	60.6	51.9	318	212	159	127	106	79.5	63.6	50.9	42.4	36.3		
	6.0	1.28	549	366	274	219	183	137	110	87.8	73.1	62.7	384	256	192	154	128	96.0	76.8	61.4	51.2	43.9		
7.0	1.55	664	443	332	266	221	166	133	106	88.6	75.9	465	310	233	186	155	116	93.0	74.4	62.0	53.1			
SJ3-VR-X1.0	1.5	0.84	360	240	180	144	120	90.0	72.0	57.6	48.0	41.1	252	168	126	101	84.0	63.0	50.4	40.3	33.6	28.8		
	2.0	1.02	437	291	219	175	146	109	87.4	69.9	58.3	50.0	306	204	153	122	102	76.5	61.2	49.0	40.8	35.0		
	2.5	1.21	519	346	259	207	173	130	104	83.0	69.1	59.3	363	242	182	145	121	90.8	72.6	58.1	48.4	41.5		
	3.0	1.41	604	403	302	242	201	151	121	96.7	80.6	69.1	423	282	212	169	141	106	84.6	67.7	56.4	48.3		
	3.5	1.62	694	463	347	278	231	174	139	111	92.6	79.3	486	324	243	194	162	122	97.2	77.8	64.8	55.5		
	4.0	1.84	789	526	394	315	263	197	158	126	105	90.1	552	368	276	221	184	138	110	88.3	73.6	63.1		
	5.0	2.33	999	666	499	399	333	250	200	160	133	114	699	466	350	280	233	175	140	112	93.2	79.9		
	6.0	2.86	1226	817	613	490	409	306	245	196	163	140	858	572	429	343	286	215	172	137	114	98.1		
7.0	3.44	1474	983	737	590	491	369	295	236	197	168	1032	688	516	413	344	258	206	165	138	118			
SJ3-VR-X2.0	1.5	2.19	939	626	469	375	313	235	188	150	125	107	657	438	329	263	219	164	131	105	87.6	75.1		
	2.0	2.58	1106	737	553	442	369	276	221	177	147	126	774	516	387	310	258	194	155	124	103	88.5		
	2.5	2.97	1273	849	636	509	424	318	255	204	170	145	891	594	446	356	297	223	178	143	119	102		
	3.0	3.36	1440	960	720	576	480	360	288	230	192	165	1008	672	504	403	336	252	202	161	134	115		
	3.5	3.74	1603	1069	801	641	534	401	321	256	214	183	1122	748	561	449	374	281	224	180	150	128		
	4.0	4.11	1761	1174	881	705	587	440	352	282	235	201	1233	822	617	493	411	308	247	197	164	141		
	5.0	7.85	3364	2243	1682	1346	1121	841	673	538	449	384	2355	1570	1178	942	785	589	471	377	314	269		
	6.0	5.58	2391	1594	1196	957	797	598	478	383	319	273	1674	1116	837	670	558	419	335	268	223	191		
7.0	6.29	2696	1797	1348	1078	899	674	539	431	359	308	1887	1258	944	755	629	472	377	302	252	216			

Note: Always double check your application rates. Tabulations are based on spraying water at 21°C. See technical information (pages 179–202) for useful formulas and other technical information.

SPEED RANGE FOR VARIOUS APPLICATION RATES

TIP PART NO.	GROUND SPEED RANGE (km/h) FOR 35 cm SPACING																GROUND SPEED RANGE (km/h) FOR 50 cm SPACING															
	100 l/ha		200 l/ha		300 l/ha		400 l/ha		500 l/ha		600 l/ha		700 l/ha		800 l/ha		100 l/ha		200 l/ha		300 l/ha		400 l/ha		500 l/ha		600 l/ha		700 l/ha		800 l/ha	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
SJ3-VR-X0.5	8.7	27	4.4	13.3	2.9	8.9	2.2	6.6	1.7	5.3	1.5	4.4	1.2	3.8	1.1	3.3	6.1	19	3.1	9.3	2.0	6.2	1.5	4.7	1.2	3.7	1.0	3.1	0.9	2.7	0.8	2.3
SJ3-VR-X1.0	14.4	59*	7.2	29	4.8	20	3.6	15	2.9	11.8	2.4	9.8	2.1	8.4	1.8	7.4	10.1	41*	5.0	21	3.4	14	2.5	10	2.0	8.3	1.7	6.9	1.4	5.9	1.3	5.2
SJ3-VR-X2.0	-	-	19	54*	12.5	36*	9.4	27	7.5	22	6.3	18	5.4	15	4.7	13.5	-	-	13	37*	8.8	25	6.6	19	5.3	15	4.4	13	3.8	11	3.3	9.4

*For safest application, recommended maximum speed is 35 km/h.